

Model	Number of vessels and dia.	Flow rate in GPM .05 micron	Required horse power	GPM required for backwashing per vessel (5 minutes) .05 micron	Manifold connection pipe size	Space required WxLxH	Shipping weight in LBS
T112	1 12" dia.	12	.75	8 (40)	1.25"	3x3x4	400
T116	1 16" dia.	30	1.0	15 (75)	1.25"	3x4x4	600
T120	1 20" dia	50	1.5	25 (125)	1.5"	4x4x6	1000
T130	1 30" dia	100	3	45 (225)	2"	4x4x7	3000
T136	1 36" dia.	140	3	70 (350)	3"	4X5X7	4000
T230	2 30" dia.	200	5	45 (450)	3"	4X8X7	5000
T236	2 36" dia.	280	7.5	70 (700)	4"	4X10X7	8000
T330	3 30" dia.	300	7.5	45 (675)	4"	4x11x7	8500
T430	4 30" dia.	400	7.5	45 (900)	4"	4x16x7	11000
T530	5 30" dia.	500	10	45 (1125)	6"	5x20x7	15000
T630	6 30" dia.	600	10	45 (1350)	6"	12x18x7	18000
T830	8 30" dia.	800	15	45 (1575)	8"	12x22x7	24000
T1030	10 30" dia.	1000	20	45 (1800)	8"	15x25x7	36000